



BRANOtect Premium (Export) Anticorrosion Fluid



■ BRANOguard

Temporary corrosion protection for the automotive, mechanical engineering and metal processing industries

■ Characteristics

Thin-bodied corrosion preventative made from mineral oil raffinates, petroleum distillates and anticorrosive additives. BRANOtect Premium contains neither silicone nor wool fat.

BRANOtect Premium builds on metal surfaces a highly effective temporary protective film against corrosion with good self-sealing tendency when breaking. Traces of moisture on metal surfaces are infiltrated.

■ Application and Dosage

Transportation protection for all metal surfaces, mass products, precision work pieces, machines, accessories, tools, measuring tools, mechanical parts.

For the conservation of all metal parts against corrosion over a long period of time, e.g., store production, spare parts storage, long mail order over different climatic zones, long storage after dispatch.

Apply through dip-and-drain, painting, or spraying. Do not apply to hot parts.

BRANOtect Premium is to be used as described above (packaging/ protection of certain kinds of metal pieces). Otherwise, no responsibility for caused damages can be taken.

■ Range of Protection

BRANOtect Premium is suitable for all metals.

■ Duration of Protection

Depending on the climate, the contamination level of the air, and the pollution condition of the metal surface.


To be regarded as indicator:

in the right package, indoors
indoors, open
in the right package, in the open
in the open, under the roof
in the open

more than 5 years
5 years
more than 5 years
5 years
several months

BRANOpac Solutions with System

According to your requirements, you have the choice between three BRANOpac solutions: BRANOpac Basic, Premium or Customized.



BRANOtect Premium (Export) Product Information

■ Delivery Forms

Containers of 10, 20, 50 or 200 litres

■ Storage

Do not store in blazing sun; always keep containers closed.

■ Operation Safety

According to the hazard substance ordinance, BRANOtect Premium is a dangerous preparation. It is flammable (R 10) and damaging to health.

Swallowing could cause damage to lungs (R 65). Do not breathe in the gas/steam/smoke/aerosol (S23). Avoid contact with skin (S24). Do not try to vomit in case of swallowing. Seek medical advice immediately and show the package or this label (S 62). Further information can be found in the safety data sheet.

■ Depreservation

Due to the thin coating, BRANOtect Premium can be easily removed with normal cleaning and degreasing procedures if necessary at all.

■ Technical Details

Density at + 20 °C:	0,84 g/cm ³
Thickness of coating:	approx. 10µm
Nature of coating:	transparent, soft gel
Time to build up the film:	approx. 2 hours
Yield:	45 m ² /l
Flash point:	> 40°C
Danger Classification (VbF):	A II, on request A III (BRANOtect Basic)
Solvent base:	no

■ Disposal

According to the German recycling and waste disposal laws (Kreislaufwirtschafts- und Abfallgesetzes), including the ordinances which go with them, used BRANOtect is a hazardous waste.

It can be supplied to suitable facilities for energy utilisation or disposal.

■ Compatibility

BRANOtect Premium does not affect most plastics or lacquers. A compatibility test is recommended for bitumen and rubber products. Natural rubbers may swell.

The information given is in line with current state of knowledge. It's non-binding and might have to be adjusted to meet local requirements. No liability is accepted for this information. Please contact us in case of doubt.

You will find more information at:
www.branopac.com or
www.branopedia.com



BRANOpac
Solutions with System

BRANOpac GmbH
Gottlieb-Daimler-Str. 18-20
35423 Lich, Germany
Phone: +49 6404 9142-0
Fax: +49 6404 9142-700
E-Mail: info@branopac.com